## **AMENDMENTS TO THE CLAIMS:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

- 1-21. (Canceled)
- 22. (Currently Amended) A solid oxide fuel cell comprising an anode, a cathode and an electrolyte, said anode and cathode arranged on opposite sides of said electrolyte, at least one of said anode and said cathode having opposite exposed and non-exposed sides, said non-exposed side being flat and said exposed side formed with a plurality of surface depressions formed in an exposed side thereof, extending only partially through into a thickness of said one of said anode and cathode.
- 23. (Original) The solid oxide fuel cell of claim 22 wherein said plurality of surface depressions are formed in the exposed side of the anode.
- 24. (Original) The solid oxide fuel cell of claim 23 wherein said surface depressions comprise an array of round holes.
- 25. (Original) The solid oxide fuel cell of claim 22 wherein said anode is substantially square.
- 26. (Original) The solid oxide fuel cell of claim 22 wherein said anode is substantially round.
- 27. (Original) The solid oxide fuel cell of claim 22 wherein said surface depressions have a depth of about 10-90% of the depth of the anode.
- 28. (Original) The solid oxide fuel cell of claim 22 wherein said anode has a thickness of from about 0.3 to about 2 mm.

DOSHI
Appl. No. 10/604,226
June 22, 2006

- 29. (Original) The solid oxide fuel cell of claim 22 wherein said surface depressions have a depth of about 0.23 mm.
- 30. (Original) The solid oxide fuel cell of claim 22 wherein said surface depressions have a depth of about 0.23 mm and said anode has a thickness of about 0.33 mm.
- 31. (Original) The solid oxide fuel cell of claim 23 wherein said anode is comprised of a ceramic tape laminated onto said electrolyte.